








<b>30</b> kN						
<b>15</b> kN	Ø156 M10(x10) mm	3/8" BSP	250 bar	3/8" BSP	200 bar	300 bar
<b>900</b> nm						
<b>21</b> kg						
<b>20</b> l/min						




Rotator's upper mount is applied in FLANGE form factor. Rotator commonly is used for rigid mounting on the crane tip or in assembly with tilt equipment. Rotator is equipped with locating pins for ease mounting. top.flange.diameter 156mm. top.flange.screw.count 10 10 screws.

Hydraulic rotator FHR 3FF is cost-effective solution generally for seasonal use in forestry, road and building construction, general cargo and material handling.



Rotator lower mount is applied in FLANGE form factor to mount direct on grapple / tool surface by fixing with screws

	
Ø (x4) mm	3/8" BSP




For additional information relating to price levels and technical data, please contact [sales@formiko.lv](mailto:sales@formiko.lv)


**Formiko Hydraulics Ltd**  
Dzirčiema Str. 119 k-1,  
Rīga LV1055 LATVIA

+371 294 49 552  
+371 264 59 383  
[sales@formiko.lv](mailto:sales@formiko.lv)  
[www.formiko.lv](http://www.formiko.lv)


On request by special conditions there are metric nipples available for rotator FHR 3FF



FORESTRY



CONSTRUCTION



Current document is automatic generated at [www.formiko.lv](http://www.formiko.lv) on 04/30/2024.  
Please always make sure that it's up to date and try to be paperless!



Hydraulic rotator FHR 3FF is cost-effective solution generally for seasonal use in forestry, road and building construction, general cargo and material handling.



Rotator's upper mount is applied in FLANGE form factor. Rotator commonly is used for rigid mounting on the crane tip or in assembly with tilt equipment. Rotator is equipped with locating pins for ease mounting. top.flange.diameter 156mm. top.flange.screw.count 10 10 screws.



Rotator lower mount is applied in FLANGE form factor to mount direct on grapple / tool surface by fixing with screws



Rotator FHR 3FF based on reliable vane type hydraulic motor which delivers torque up to 900Nm at 25MPa.



Rotator for shipping is packed in compact solid cardboard box with dimensions 340x230x240mm.



We providing TWO year warranty for this rotator.

For additional information relating to price levels and technical data, please contact [sales@formiko.lv](mailto:sales@formiko.lv)

**Formiko Hydraulics Ltd**

Dzirčiema Str. 119 k-1,  
Rīga LV1055 LATVIA

+371 294 49 552

+371 264 59 383

[sales@formiko.lv](mailto:sales@formiko.lv)

[www.formiko.lv](http://www.formiko.lv)

On request by special conditions there are metric nipples  
available for rotator FHR 3FF



FORESTRY



CONSTRUCTION

